



(slika je simbolična)

Filter z aktivnim ogljem »FUTURA-mali« Kov. pos. Vel.0,G1/4

Kategorija: [Activated carbon filter with metal bowl](#)
Šifra: **142454RIE**

Kratek opis

Active charcoal filter »FUTURA-mini«, Metal container, 0.005 mg/m³, Size 0, G 1/4, Input pressure 0 - 12 bar, Temp. -10°C to 50°C

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar
Merjenje pretoka	G 1/4 PA66 GF60 Metal container
Navoj	Plastic
Ohišje	FUTURA-mini
Posoda	Compressed air, neutral gases
Priključni navoj	NBR
Serijska	
Srednje	
Tesnilo	
Vsebnost olja v ostanku [mg/m ³]	0.005
Max. vhodni tlak [bar]	12
C [mm]	27.0
A [mm]	43.0
Max. temperaturno območje [°C]	50
B [mm]	114.0
Pretok [l/min]	470