



Filter z aktivnim ogljem »FUTURA-mali« PC zbir. Vel. 0, G1/4

Kategorija: [Activated carbon filter with polycarbonate bowl](#)
Šifra: **142453RIE**

(slika je simbolična)

Kratek opis

Active charcoal filter »FUTURA-mini« with PC container, 0.005 mg/m³, Size 0, G 1/4, Input pressure 0 - 12 bar, Temp. -10°C to 50°C
Activated carbon filters in modern design for compliance with strict compressed air purity requirements.
Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

| | |
|--|--|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Activated carbon At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar |
| Merjenje pretoka | G 1/4 PA66 GF60 Polycarbonate container |
| Navoj | Plastic |
| Ohišje | FUTURA-mini |
| Posoda | Compressed air, neutral gases |
| Priključni navoj | NBR |
| Serijska | |
| Srednje | |
| Tesnilo | |
| Vsebnost olja v ostanku [mg/m ³] | 0.005 |
| Max. vhodni tlak [bar] | 12 |
| C [mm] | 27.0 |
| A [mm] | 43.0 |
| Max. temperaturno območje [°C] | 50 |
| B [mm] | 125.0 |
| Pretok [l/min] | 470 |