

Datum: 03.07.2024



[Filter z aktivnim ogljem »multifix«PC zbir.Vel.1,G 1/4](#)

Kategorija: [Activated carbon filter with PC bowl, bowl guard](#)
Šifra: **100541RIE**

(slika je simbolična)

Kratek opis

Active charcoal filter »multifix« with PC container and protective cage, 0.005 mg/m³, Size 1, G 1/4, Input pressure max. 16 bar

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

Tehnične Specifikacije

Element filtra	Activated carbon-POM
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Navoj	G 1/4
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage
Serija	multifix
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	1
DN	6
Max. vhodni tlak [bar]	16
C [mm]	27.0
A [mm]	47.8
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	109.8
B [mm]	136.8
Pretok [l/min]	380