

Datum: 27.12.2024



[Filter z aktivnim ogljem »multifix«PC zbir.Vel. 3G 1/2](#)

Kategorija: [Activated carbon filter with PC bowl, bowl guard](#)
Šifra: **100542RIE**

(slika je simbolična)

Kratek opis

Active charcoal filter »multifix« with PC container and protective cage, 0.005 mg/m³, Size 3, G 1/2, Input pressure max. 16 bar
For filtering odours out of compressed air.
The activated carbon absorbs the oil vapour molecules contained in the compressed air.
A separate filter route prevents activated carbon particles from entering the air flow.

Tehnične Specifikacije

Element filtra	Activated carbon-POM
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Navoj	G 1/2
Ohišje	Die-cast zinc
Posoda	Polycarbonate container with protective cage
Serija	multifix
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	3
DN	15
Max. vhodni tlak [bar]	16
C [mm]	34.5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	68.8
D [mm]	132.5
B [mm]	167.0
Pretok [l/min]	1500