

Datum: 02.10.2024



(slika je simbolična)

## Filter z aktivnim ogljem »variobloc«PC zbir.Vel.2,G 1/2

Kategorija: [Activated carbon filter with polycarbonate bowl](#)  
Šifra: **100694RIE**

### Kratek opis

Active charcoal filter »variobloc« with PC container, 0.003 mg/m<sup>3</sup>, Size 2, G 1/2, Input pressure max. 16 bar, Temp. max. 50 °C

Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

### Tehnične Specifikacije

Kakovost zraka po ISO 8573.1	Class 1 dirt, class 1 oil
Merjenje pretoka	At P <sub>1</sub> = 7 bar and pressure drop Δp = 0,2 bar
Navoj	G 1/2
Posoda	Polycarbonate container
Serija	variobloc
Vsebnost olja v ostanku [mg/m <sup>3</sup> ]	0.003
Velikost	2
Max. vhodni tlak [bar]	16
C [mm]	26.0
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	70.0
B [mm]	193.0
Pretok [l/min]	1200