

Datum: 03.11.2024



(slika je simbolična)

## [Glicerinski man.cent. priklop zadaj G 1/4, 0 - 4 bar, Ø 63](#)

Kategorija: [Wika](#)  
Šifra: **102147RIE**

### Kratek opis

Glycerine pressure gauge, CrNi steel housing, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0 - 4 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	CrNi steel, with bare metal surface
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	Transparent plastic
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Stisnjen okvir	CrNi steel, with glossy metal surface (3-hole bezel)
Stopnja rasti na območju skale - bar [bar]	0.2
Razred točnosti	1.6
Merilno območje max. bar	4
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premer [mm]	63
Vrsta	213.53