

Datum: 27.07.2024

(slika je simbolična)

Glicerinski manometer, CrNi jeklo, G 1/2, 0 - 6 bar, Ø 100

Kategorija: [Wika](#)
Šifra: **102395RIE**

Kratek opis

Glycerine pressure gauge, CrNi steel safety design,
Connection radial bottom, G 1/2, Measurement range 0 - 6
bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge, CrNi steel
type, with solid baffle wall and blow-out (safety housing).
Suitable for gaseous or liquid, corrosive and crystallising
media which do not have high viscosity, also in corrosive
atmosphere.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Laminated safety glass
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.1
Razred točnosti	1.0
Merilno območje max. bar	6
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	100
Premer [mm]	100
Vrsta	233.30