



(slika je simbolična)

## Glicerinski manometer, priklp spodaj, G 1/4, 0 - 60 bar, Ø 63

Kategorija: [Wika](#)  
Šifra: **102177RIE**

### Kratek opis

Glycerine pressure gauge with metal housing, Connection radial bottom, G 1/4, Goods class 1.6, Measurement range 0 - 60 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|  |                   |
|--|-------------------|
| Min. sobna temperatura [°C]                | -20               |
| Min. temperatura medija [°C]               | -20               |
| Material Prozessanschluss                  | Copper alloy      |
| Merilni element                            | Copper alloy      |
| Ohišje                                     | Hot-pressed brass |
| Položaj povezave                           | radial on bottom  |
| Povezava                                   | G 1/4             |
| Prednje steklo                             | Plexiglass        |
| Premikanje                                 | Copper alloy      |
| Spodnja/Zgornja meja območja               | Positive pressure |
| Stisnjen okvir                             | CrNi steel        |
| Razred točnosti                            | 1.6               |
| Stopnja rasti na območju skale - bar [bar] | 2                 |
| Max. sobna temperatura [°C]                | 60                |
| Max. temperatura medija [°C]               | 60                |
| Merilno območje max. bar                   | 60                |
| Premer [mm]                                | 63                |
| Vrsta                                      | 213.40            |