

Datum: 22.07.2024



(slika je simbolična)

Glicerinski manometer, sprednji obroč, G 1/2, 0 - 1.6 bar, Ø 100

Kategorija: [Glycerine pressure gauges, hot-pressed brass house](#)
Šifra: **102261RIE**

Kratek opis

Glycerine pressure gauge, front ring, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measurement range 0 - 1.6 bar, Ø 100

Bourdon-tube pressure gauge in standard design, with panel-mounting bezel made of chrome-plated and polished steel.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

| | |
|--|-------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Material Prozessanschluss | Copper alloy |
| Merilni element | Copper alloy |
| Ohišje | Hot-pressed brass |
| Položaj povezave | rear, excentrical |
| Povezava | G 1/2 |
| Prednje steklo | Plexiglass |
| Premikanje | Copper alloy |
| Spodnja/Zgornja meja območja | Positive pressure |
| Stopnja rasti na območju skale - bar [bar] | 0.05 |
| Razred točnosti | 1.0 |
| Merilno območje max. bar | 1.6 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Premer [mm] | 100 |
| Vrsta | 213.40 |