

Datum: 24.08.2024



(slika je simbolična)

Glicerinski manometer, sprednji obroč, G 1/4, 0 - 160 bar, Ø 63

Kategorija: [Wika](#)
Šifra: **102256RIE**

Kratek opis

Glycerine pressure gauge, front ring, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0 - 160 bar, Ø 63

Bourdon-tube pressure gauge in standard design, with panel-mounting bezel made of chrome-plated and polished steel.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Hot-pressed brass
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	Plexiglass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Razred točnosti	1.6
Stopnja rasti na območju skale - bar [bar]	5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premer [mm]	63
Merilno območje max. bar	160
Vrsta	213.40