

Datum: 03.07.2024



(slika je simbolična)

Glicerinski manometer, sprednji obroč, G 1/4, -1 / 0 bar, Ø 63

Kategorija: [Wika](#)
Šifra: **102246RIE**

Kratek opis

Glycerine pressure gauge, front ring, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range -1 / 0 bar, Ø 63

Bourdon-tube pressure gauge in standard design, with panel-mounting bezel made of chrome-plated and polished steel.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

| | |
|--|-------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Merilno območje min. bar | -1 |
| Material Prozessanschluss | Copper alloy |
| Merilni element | Copper alloy |
| Ohišje | Hot-pressed brass |
| Položaj povezave | rear, central |
| Povezava | G 1/4 |
| Prednje steklo | Plexiglass |
| Premikanje | Copper alloy |
| Spodnja/Zgornja meja območja | Vacuum |
| Stopnja rasti na območju skale - bar [bar] | 0.05 |
| Razred točnosti | 1.6 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Premer [mm] | 63 |
| Vrsta | 213.40 |