

Datum: 24.08.2024



(slika je simbolična)

Hitre spojke I.D. 10, /poniklanaMedenina, I.D.10

Kategorija: [Quick disconnect coupling DN 10, with hose stem](#)
Šifra: **141559RIE**

Kratek opis

Quick-connect coupling I.D. 10, Steel / nickel-plated brass,
Sleeve I.D. 10, Operating pressure 0 - 35 bar, Temp. -20 °C
to 100 °C

"
Single-sided blocking and robust quick connect coupling
with high flow performance.

To prevent injuries or a "whiplash" effect, we recommend
that the plug-in nipple is held with one hand during
uncoupling.

These quick disconnect couplings are not suitable for direct
attachment to pulsating tools.

We recommend using our vibration dampers, according to
ISO 6150 § 7.1.

Areas of application: Pneumatic system, Machine and plant
engineering, Measurement, monitoring and control systems,
manufacturing industry, medical technology, chemical /
pharmaceutical industry, workshops, automotive, food
technology, aerospace.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 - 35 bar at 6 bar and $\Delta_p = 0.5$ bar
Merjenje pretoka	
Navojni kos	Nickel-plated brass
Ohišje	Nickel-plated brass
Povezava	I.D. 10
Rokav	Galvanised steel
Tesnilo	NBR
Ventil	Nickel-plated brass
Vzmet	Stainless steel
DN	10
a/f [mm]	24
Dolžina [mm]	75.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	3500 l/min (air)