

Datum: 03.07.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Hitre spojke I.D. 5, ponikljana medenina, cev I.D. 9

Kategorija: [Quick disconnect coupling DN 5, with hose stem](#)
Šifra: **107168RIE**

Kratek opis

Quick-connect coupling I.D. 5, nickel-plated brass, Sleeve I.D. 9, Operating pressure 0-35 bar, Med./ambient temp. -20°C to 100°C

"

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	I.D. 9
Pritrdilni obroč	Stainless steel
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
Dolžina [mm]	46.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	560 l/min (air)