

Datum: 03.07.2024



(slika je simbolična)

[Hitre spojke I.D. 5, zunanji navoj medenina, toga, cev 6x4](#)

Kategorija: [Quick disconnect coupling DN 5 with hose connector](#)
Šifra: **107141RIE**

Kratek opis

Quick-connect coupling I.D. 5, bright brass, rigid, Hose connection 6x4, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

"

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla | Stainless steel |
| Merjenje pretoka | at 6 bar and $\Delta p = 0.5$ bar |
| Ohišje | Brass with a bare metal surface |
| Povezava | Hose connection 6x4 |
| Pritrdilni obroč | Stainless steel |
| Različica | Rigid |
| Rokav | Brass with a bare metal surface |
| Telo ventila | Brass with a bare metal surface |
| Tesnilo | NBR |
| Vzmet | Stainless steel |
| DN | 5 |
| a/f [mm] | 14 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |
| Dolžina [mm] | 120.0 |
| Pretok | 560 l/min (air) |