

Datum: 24.08.2024



(slika je simbolična)

Hitre spojke I.D. 7.2, cev 10 mm, vrteče

Kategorija: [Quick disconnect coupling DN 7.2, swivel type](#)
Šifra: **107298RIE**

Kratek opis

Quick-connect coupling I.D. 7.2, nickel-plated brass, Sleeve 10 mm rotating, Operating pressure 0 - 35 bar, Temp. 0 °C to 70 °C

" Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

"

Tehnične Specifikacije

Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	Stem 10 mm, swivel type
Pritrdilni obroč	Stainless steel 1.4310
Rokav	Nickel-plated brass
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel 1.4310
Zaporni zatič	Stainless steel 1.4034
DN	7.2
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
Dolžina [mm]	74.0
Pretok	1000 l/min (air)