

Datum: 24.08.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Hitre spojke I.D. 7.2 zakl. na obeh str.G 1/2 N.N.

Kategorija: [Quick disconnect coupl. DN7.2, bright brass female](#)  
Šifra: **107511RIE**

### Kratek opis

Quick-connect coupling I.D. 7.2, locking on both sides, Bright brass, G 1/2 IT, Operating pressure 0-35 bar, Temp. -20°C to 100°C  
Couplings, stems and plugs are fitted with a valve.  
Connection: Both valves open and the medium is allowed to pass.  
Disconnection: Both valves close and the medium is prevented from escaping.  
Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.2
a/f [mm]	24
Dolžina [mm]	42.5
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	700 l/min (air)