

Datum: 03.07.2024



## Hitre spojke I.D. 7.2Z.N. Med.G 1/4 N.N.

Kategorija: [Quick disconnect coupling DN 7.2, female](#)  
Šifra: **107211RIE**

(slika je simbolična)

### Kratek opis

Quick-connect coupling I.D. 7.2, bright brass, G 1/4 IT,  
Operating pressure 0 - 35 bar, Med./ambient temp. -20 °C to  
100 °C

"

Universal, one-hand quick disconnect couplings, one side  
sealing, suitable for a wide range of tasks and applications!  
The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

These quick disconnect couplings are not suitable for direct  
attachment to pulsating tools.

We recommend using our vibration dampers, according to  
ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant  
engineering, measurement, monitoring and control systems,  
manufacturing industry, medical technology, chemical /  
pharmaceutical industry, workshops, automotive.

"

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
Zaporni zatič	Stainless steel
DN	7.2
a/f [mm]	22
Dolžina [mm]	41.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	1000 l/min (air)