

Datum: 24.08.2024



(slika je simbolična)

Hitre spojke I.D. 7.8, , G 1/4 notranji navoj

Kategorija: [Quick disconnect coupling DN 7.8, female](#)
Šifra: **141515RIE**

Kratek opis

Quick-connect coupling I.D. 7.8, Steel, G 1/4 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

Single-sided blocking, high quality and robust quick connect coupling for high flow values.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, mining.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 - 35 bar
Krogla	Stainless steel at 6 bar and $\Delta_p = 0.5$ bar
Merjenje pretoka	Galvanised steel
Navojni kos	Galvanised steel
Ohišje	G 1/4 IT
Povezava	Galvanised steel
Rokav	NBR
Tesnilo	Die-cast zinc (zamac)
Ventil	Stainless steel
Vzmet	7.8
DN	19
a/f [mm]	54.0
Dolžina [mm]	100
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	2000 l/min (air)