

Datum: 01.10.2024



(slika je simbolična)

[Hitre spojke I.D. 7.8, Nerjavno jeklo 1.4305, G 1/2 zunanji navoj](#)

Kategorija: [Quick disconnect coupling DN 7.8, 1.4305, male](#)
Šifra: **107419RIE**

Kratek opis

Quick-connect coupling I.D. 7.8, Stainless steel 1.4305, G 1/2 ET, Operating pressure 0 - 35 bar, Temp. -15 °C to 200 °C

"

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, manufacturing industry, medical technology, chemical / pharmaceutical industry, food technology, aerospace, mining, offshore.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Stainless steel 1.4305
Povezava	G 1/2 ET
Pritrdilni obroč	Stainless steel
Rokav	Stainless steel 1.4305
Telo ventila	Stainless steel 1.4305
Tesnilo	FKM
Vzmet	Stainless steel
DN	7.8
a/f [mm]	24
Dolžina [mm]	60.5
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200
Pretok	1800 l/min (air)