

Datum: 05.02.2025



## Hitre spojke I.D. 5 »connect line«, G 3/8 notranji navoj

Kategorija: [Quick disconnect coupling DN 5, female](#)  
Šifra: **115631RIE**

(slika je simbolična)

### Kratek opis

Quick-connect coupling I.D. 5 »connect line«, nickel-plated brass, G 3/8 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

Low-priced, one-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	G 3/8 IT
Pritrdilni obroč	Stainless steel
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
Zaporni zatič	Stainless steel
DN	5
a/f [mm]	19
Dolžina [mm]	37.4
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	560 l/min (air)