

Datum: 24.08.2024



(slika je simbolična)

Javljal. kon. položaja tip SC-D 2, induktiven senzor, 3-wire, PNP

Kategorija: [End position feedback aluminium, inductive sensors](#)
Šifra: **103692RIE**

Kratek opis

End position feedback type SC-D 2, inductive sensors, 3-wire, PNP NO contact, 10 V-30 V DC, 100 mA, IP 66, Temp. -20 °C to 70 °C
Robust type in an aluminium housing
- Universal indicator for NAMUR sizes 80 x 30 and 130 x 30
- Height-adjustable feet that adapt to different pinion projections
- ON / OFF position indicator also visible from a distance
- Easy-to-adjust, self-locking trip cam

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20 |
| Gred | Nickel-plated steel |
| IP zaščita | EX TDA21 IP66/67 T 85 °C |
| Kabelska uvodnica | M20x1.5, up to four cable glands possible |
| Obratovalni tok | Max. 100 mA |
| Ohišje | Die-cast aluminium EN AB 46100, epoxy powder-coated |
| Opis | End position feedback, SC-D 2 type with inductive 3-wire sensors |
| Preklopna funkcija | PNP NO contact with inductive sensors, 3-wire |
| Različica | Stainless steel |
| Vijaki | 10 V - 30 V DC |
| Območje napetosti | 70 |
| Max. temperaturno območje [°C] | |