



(slika je simbolična)

## Javljal.kon.položaja ATEX tip N 2, induktiven NAMUR senzor

Kategorija: [End position feedback, ATEX](#)Šifra: **103690RIE**

### Kratek opis

End position feedback ATEX type N 2, inductive NAMUR sensors, Nominal voltage 8 V DC, 1 mA - 3 mA, Temp. -20 °C to 70 °C

Robust type in a plastic housing- Universal indicator for NAMUR sizes 80 x 30 and 130 x 30- Height-adjustable feet that adapt to different pinion projections- ON / OFF position indicator also visible from a distance- Easy-to-adjust, self-locking trip cam

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Glava	Polycarbonate, transparent
Gred	Polyamide PA6, black
IP zaščita	IP 67, acc. to DIN EN 60529
Izhodni tok	Damped <1 mA / undamped >3 mA
Kabelska uvodnica	M20x1.5
Montažni most	PA6 with 30 % glass fibre
Napajanje	Rated voltage 8 VDC
Ohišje	Polyamide blue or black
Opis	End position feedback, with inductive NAMUR sensors, ATEX
Preklopna funkcija	Damped or undamped in the end position
Različica	with inductive NAMUR sensors, ATEX
Tesnilo	EPDM and NBR
Vijaki	Stainless steel 1.4301
Max. temperaturno območje [°C]	70