

Datum: 24.08.2024



(slika je simbolična)

## Kaljena spojka DN6Z.N.blokirni ventil,Med.G 1/4 ravent

Kategorija: [Temp. control coupl. DN 6, ET, with shut-off valve](#)  
Šifra: **107918RIE**

### Kratek opis

Tempered coupling DN 6, Exterior thread, Blocking valve, Brass, G 1/4 straight, Operating press. max. 15 bar, Temp. -20°C to 160°C  
Compatible with HASCO Z 8 system.  
For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.  
Optionally with free passage, one or both sides sealing.  
Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Priključni navoj	G 1/4 straight
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Max. obratovalni tlak [bar]	15
a/f [mm]	17
Dolžina [mm]	48.0
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160