


Datum: 24.08.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Kaljeni vtični konektor DN 6, zunanji navoj, M14x1.5, dolžina 15

Kategorija: [Push-in plug DN 6, without shut-off valve, ET](#)  
Šifra: **107933RIE**

(slika je simbolična)

### Kratek opis

Tempered plug-in nipple DN 6, Exterior thread, Brass, M14x1.5, AF 15, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Navoj	M14x1.5
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
a/f [mm]	15
Max. obratovalni tlak [bar]	15
Dolžina [mm]	26.0
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160