

Datum: 24.08.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## [Kamlok Hitro spajane spojka, C tip, Alu, I.D. 38, for plug Ø 53](#)

Kategorija: [Kamlok female coupler with hose stem, Part C](#)  
Šifra: **108029RIE**

### Kratek opis

Kamlok quick-connect socket, Hose supports, C type, Aluminium, Hose I.D. 38, for plug Ø 53 mm, Operating pressure max. 16 bar  
Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.  
A male part and a female part are joined together by shifting the handles.  
There is no need to turn the hose!  
Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.  
All Kamlok quick coupling boxes and Kamlok closure boxes are supplied with NBR seal.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
Za cev I.D.	38
Za vtič Ø [mm]	53
Max. temperaturno območje [°C]	68
A [mm]	87.4
C [mm]	116.5