

Datum: 03.07.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## [Kamlok Hitro spajane spojka z notranji navoj, D tip, 1.4401, G 4](#)

Kategorija: [Kamlok female coupler, female threaded, Part D](#)  
Šifra: **108122RIE**

### Kratek opis

Kamlok quick-connect socket with interior thread, D type, Stainless steel 1.4401, G 4, for plug Ø 120 mm, Pressure max. 16 bar

High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection.

A male part and a female part are joined together by shifting the handles.

There is no need to turn the hose!

Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc.

All Kamlok quick coupling boxes and Kamlok closure boxes are supplied with NBR seal.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 4
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
C [mm]	90.0
Max. temperaturno območje [°C]	95
Za vtič Ø [mm]	120
A [mm]	159.9