

Datum: 02.10.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 100hod 50G 1/4

Kategorija: [Compact cylinder, double-acting, with magnet](#)  
Šifra: **115250RIE**

### Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 100, Stroke 50, Connection G 1/4, Working pressure 1-10 bar, Temp. -20 °C to 70 °C  
Characterised by a very short and compact design.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel
Batnica IT	M12x1.75
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Aluminium
Ovoj	G 1/4
Povezava	ACP series
Serija	NBR
Tesnilo	1
Min. delovni tlak [bar]	10
Max. delovni tlak [bar]	25
Batnica Ø [mm]	50
Stroke [mm]	70
Max. temperaturno območje [°C]	100
Bat Ø [mm]	