



## Komp. cilind. del. v dveh smereh, bat Ø 12 hod 5,M5,ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)  
Šifra: **155566RIE**

(slika je simbolična)

### Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ12, Stroke5, M5, Work.press.max.10bar, Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M5x0.8
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	M5
Serija	ACE series
Standard	acc. to ISO 21287
Tesnilo	NBR
Stroke [mm]	5
Max. delovni tlak [bar]	10
Bat Ø [mm]	12
Max. temperaturno območje [°C]	70