



(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 20hod 55M5x0,8

Kategorija: [Compact cylinder, double-acting, with magnet](#)  
Šifra: **115295RIE**

### Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 20, Stroke 55, Connection M5x0,8, Working pressure 1-10 bar, Temp. -20 °C to 70 °C

Characterised by a very short and compact design.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                               |
|--------------------------------|-------------------------------|
| Min. temperaturno območje [°C] | -20                           |
| Bat                            | Aluminium                     |
| Batnica                        | Steel                         |
| Batnica IT                     | M5x0.8                        |
| Ffunkcija                      | double-acting                 |
| Gewinde Kolbenstange           | female piston rod with magnet |
| Magnet                         | Aluminium                     |
| Ovoj                           | M5x0.8                        |
| Povezava                       | ACP series                    |
| Serija                         | NBR                           |
| Tesnilo                        | 1                             |
| Min. delovni tlak [bar]        | 10                            |
| Batnica Ø [mm]                 | 10                            |
| Max. delovni tlak [bar]        | 20                            |
| Bat Ø [mm]                     | 55                            |
| Stroke [mm]                    | 70                            |
| Max. temperaturno območje [°C] | 70                            |