

Datum: 03.07.2024



## Komp. cilind. del. v dveh smereh, bat Ø 25, hod 100, M5, ISO 21287

Kategorija: [Compact cylinders double-acting, female piston rod](#)  
Šifra: **155377RIE**

(slika je simbolična)

### Kratek opis

Compact cyl. ISO 21287, double-acting, female piston rod, magnet, Piston Ø 25, Stroke 100, M5, Work.press.max. 10 bar, Temp. -20°C to 70°C. Series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M6x1.0
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	M5
Povezava	ACE series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	10
Max. delovni tlak [bar]	25
Bat Ø [mm]	70
Max. temperaturno območje [°C]	100
Stroke [mm]	