

Datum: 02.10.2024



(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 32hod 60G 1/8

Kategorija: [Metalwork](#)
Šifra: **105993RIE**

Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 32, Stroke 60, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 60°C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	POM
Batnica	C45 steel, hard chrome-plated
Batnica IT	M8
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	LINER series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	0.6
Min. nastavljeni tlak [bar]	10
Max. delovni tlak [bar]	32
Bat Ø [mm]	60
Max. temperaturno območje [°C]	60
Stroke [mm]	60