

Datum: 15.01.2025



(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 50hod 60G 1/8

Kategorija: [Metalwork](#)
Šifra: **106013RIE**

Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 50, Stroke 60, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 60°C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Bat | POM |
| Batnica | C45 steel, hard chrome-plated |
| Batnica IT | M10 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | female piston rod with magnet |
| Magnet | Anodised aluminium jacket with T-slots |
| Ovoj | G 1/8 |
| Povezava | LINER series |
| Serija | acc. to ISO 21287 |
| Standard | NBR |
| Tesnilo | 0.4 |
| Min. nastavljeni tlak [bar] | 10 |
| Max. delovni tlak [bar] | 50 |
| Bat Ø [mm] | 60 |
| Max. temperaturno območje [°C] | 60 |
| Stroke [mm] | 60 |