

Datum: 15.01.2025



## Komp. cilind. del. v dveh smereh, bat Ø63, hod15, G1/8, ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)  
Šifra: **155704RIE**

(slika je simbolična)

### Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ63, Stroke15, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M12x1.25
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serija	ACE series
Standard	acc. to ISO 21287
Tesnilo	NBR
Max. delovni tlak [bar]	10
Stroke [mm]	15
Bat Ø [mm]	63
Max. temperaturno območje [°C]	70