

**Datum:** 24.08.2024

## **Komp. cilind. del. v dveh smereh, bat** **Ø80, hod70, G1/8, ISO21287**

Kategorija: [Compact cylinders double-acting, male piston rod](#)  
Šifra: **155740RIE**

(slika je simbolična)

### **Kratek opis**

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ80, Stroke70, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### **Tehnične Specifikacije**

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M16x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serija	ACE series
Standard	acc. to ISO 21287
Tesnilo	NBR
Max. delovni tlak [bar]	10
Max. temperaturno območje [°C]	70
Stroke [mm]	70
Bat Ø [mm]	80