

**Datum:** 02.10.2024

(slika je simbolična)

## [komp. cilinder LINERdelujoč v dveh smerehbat Ø 20hod 60M5](#)

Kategorija: [Metalwork](#)  
Šifra: **105975RIE**

### Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 20, Stroke 60, M5, Working pressure max. 10 bar, Temp. -10°C to 60 °C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	POM
Batnica	C45 steel, hard chrome-plated
Batnica IT	M6
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	M5
Povezava	LINER series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	0.6
Min. nastavljeni tlak [bar]	10
Max. delovni tlak [bar]	20
Bat Ø [mm]	20
Max. temperaturno območje [°C]	60
Stroke [mm]	60