



(slika je simbolična)

## [komp.cilinder,enosmerni,zunanjiP-Ø40, hod 20, G1/8, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, female](#)  
Šifra: **155931RIE**

### Kratek opis

Compact cyl.ISO 21287,single-acting,female piston rod, ext.,magnet,PistonØ40,Stroke20,G1/8,Work.press.max.10bar,Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M8x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	ATE series
Serija	acc. to ISO 21287
Standard	pressureless in the extended position
Starting position	NBR
Tesnilo	10
Max. delovni tlak [bar]	20
Stroke [mm]	40
Bat Ø [mm]	70
Max. temperaturno območje [°C]	