

Datum: 02.10.2024



(slika je simbolična)

Kompakt.ejektor CP digi. vakum. stikalo, velikost šobe 1.5 mm

Kategorija: [Compact ejector »CP«](#)
Šifra: **108409RIE**

Kratek opis

Compact ejector »CP«, Digital vacuum switch, Nozzle size 1.5 mm, NC, Compressed air / vacuum conn. G 1/8 IT, PN 5 bar

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Properties:

- Vacuum generator with integrated control valves and system monitoring functions
- Gripping and blowing off can be controlled without the need for external valves
- Optimised air consumption thanks to many models with differing suction capacities
- Minimum energy costs in continuous operation thanks to automatic air-saving
- Easy adjustment with foil keypad and LED display of the settings

Applications:

Handling of air-tight or slightly porous workpieces in fully automated handling systems, e.g. in the robotics, automotive, packaging, electronics, electrical engineering and metalworking industries.

Tehnične Specifikacije

Dovod stisnjenega zraka	G 1/8 IT
Dovod vakuuma	G 1/8 IT
	NC blow-off valve, filter, silencer, non-return valve
Integrirano	
Položaj sesalnega ventila v mirovanju	NC
Telo	Anodised aluminium
Velikost šobe [mm]	1.5
Max. obratovalni tlak [bar]	5
Premer [mm]	20.0
Max. stopnja sesanja [l/min]	65
Dolžina [mm]	72.0
Poraba zraka med evakuacijo [l/min]	117
Višina [mm]	164.0
Teža [g]	275.0