

Datum: 02.01.2025



## Kompaktni cilindri, enosmerni, P-Ø100, hod 20, G1/8, ISO21287

Kategorija: [Compact cylinders, single-acting, retracted, male](#)  
Šifra: **155904RIE**

(slika je simbolična)

### Kratek opis

Compact cyl.ISO 21287,single-acting, male piston rod,retr.,magnet,PistonØ100,Stroke20,G1/8,Work.press.max .10bar,Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M16x1.5
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serija	ASE series
Standard	acc. to ISO 21287
Starting position	pressureless in the retracted position
Tesnilo	NBR
Max. delovni tlak [bar]	10
Stroke [mm]	20
Max. temperaturno območje [°C]	70
Bat Ø [mm]	100