

Datum: 03.07.2024

Kot. varnos. ventil, za tekoč., G 1 1/2, vkl. prit. 15 bar

Kategorija: [Angle-tip Varnostni ventil G 1 1/2](#)
Šifra: **105635RIE**

(slika je simbolična)

Kratek opis

Corner safety valve, for liquids, Red brass, FPM, Operating temp. -10 °C to 110 °C, G 1 1/2, AF 58, Trigger pressure 15 bar
For non-toxic, non-flammable liquids.
No evaporation allowed when blowing off.
With diaphragm to protect the spring and with lifting device.
Type-tested, TÜV-SV. 749. F

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Membrane	FPM
Navoj	G 1 1/2
Notranji deli	Brass
Ohišje	Bronze
Vstop in izstop	Each with female thread type G acc. to DIN EN ISO 228-1
Vzmet	C steel
Vzmet pokrova motorja	Brass
Min. prilagoditveno območje [bar]	1
Min. nastavljeni tlak [bar]	15
Max. območje nastavitve [bar]	16
L2 [mm]	40.0
L1 [mm]	48.0
a/f [mm]	58
Max. delovna temperatura [°C]	110
H [mm]	175.0