

**Datum:** 24.08.2024

(slika je simbolična)

## Kot. varnos. ventil, za tekoč., G 1/2, vkl. prit. 16 bar

Kategorija: [Angle-tip Varnostni ventil G 1/2](#)  
Šifra: **105559RIE**

### Kratek opis

Corner safety valve, for liquids, Red brass, FPM, Operating temp. -10 °C to 110 °C, G 1/2, AF 27, Trigger pressure 16 bar  
For non-toxic, non-flammable liquids.  
No evaporation allowed when blowing off.  
With diaphragm to protect the spring and with lifting device.  
Type-tested, TÜV-SV. 749. F

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Membrane	FPM
Navoj	G 1/2
Notranji deli	Brass
Ohišje	Bronze
Vstop in izstop	Each with female thread type G acc. to DIN EN ISO 228-1
Vzmet	C steel
Vzmet pokrova motorja	Brass
Min. prilagoditveno območje [bar]	1
Max. območje nastavitve [bar]	16
Min. nastavljeni tlak [bar]	16
L2 [mm]	20.0
L1 [mm]	25.0
a/f [mm]	27
H [mm]	92.0
Max. delovna temperatura [°C]	110