



(slika je simbolična)

Kot. varnos. ventil, za tekoč., G 2, vkl. prit. 1.5 bar

Kategorija: [Angle-tip Varnostni ventil G 2](#)
Šifra: **137686RIE**

Kratek opis

Corner safety valve, for liquids, Red brass, NBR, Operating temp. -10 °C to 110 °C, G 2, AF 70, Trigger pressure 1.5 bar
For non-toxic, non-flammable liquids.
No evaporation allowed when blowing off.
With diaphragm to protect the spring and with lifting device.
Type-tested, TÜV-SV. 749. F

Tehnične Specifikacije

| | |
|-----------------------------------|---|
| Min. delovna temperatura [°C] | -10 |
| Membrane | NBR |
| Navoj | G 2 |
| Notranji deli | Brass |
| Ohišje | Bronze |
| Vstop in izstop | Each with female thread type G acc. to DIN EN ISO 228-1 |
| Vzmet | C steel |
| Vzmet pokrova motorja | Brass |
| Min. prilagoditveno območje [bar] | 1 |
| Min. nastavljeni tlak [bar] | 1.5 |
| Max. območje nastavitve [bar] | 10 |
| L2 [mm] | 48.0 |
| L1 [mm] | 56.0 |
| a/f [mm] | 70 |
| Max. delovna temperatura [°C] | 110 |
| H [mm] | 200.0 |