

Datum: 24.08.2024



krog. ventil med., pnevm. vklop enojno delovanje, 3/4

Kategorija: [Brass ball valve, single-acting actuator](#)Šifra: **103573RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Pneumat. actuation drive, single-acting,
Operating temperature -20 °C to 150 °C, Rp 3/4, DN 20, PN
max. 16 bar

Ball valves with pneumatic actuator.

Pneumatic, double-piston, part-turn actuator, double-rocker
principle.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperaturno območje [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 3/4
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Max. vodeni tlak [bar]	5.6
Max. obratovalni tlak [bar]	16
DN	20
L [mm]	77.0
Max. temperaturno območje [°C]	80
Kot vrtenja [°]	90
B [mm]	117.0
Max. delovna temperatura [°C]	150
A [mm]	221.0