

Datum: 03.07.2024



(slika je simbolična)

## krog. ventil med., pnevm. vklop vzmetni preklop, 1 1/2

Kategorija: [Brass ball valve, single-acting actuator](#)Šifra: **103536RIE**

### Kratek opis

2-way brass ball valve Pneumat. actuation drive spring switching, Operating temp. max. 70°C, Rp 1 1/2, DN 40, PN max. 25 bar  
2-way cock, full bore.  
Pneumatic actuators, double- or single acting version and integrated end-position feedback.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Adapter ventila	Supplied as standard
Material krogelnega ventila	Nickel-plated brass, with ISO flange plate
Navoj	Rp 1 1/2
Pogonski material	Anodised aluminium
Premaz za krogelni ventil	PTFE / FKM
Premaz za pogon	NBR
Različica	single-acting - spring to close
Priporočeni vodeni tlak [bar]	5.5
Max. vodeni tlak aktuatorja [bar]	10
PN [bar]	25
D [mm]	36.0
DN	40
a/f [mm]	55
Max. delovna temperatura [°C]	70
Kot vrtenja [°]	90
L [mm]	120.0
A [mm]	137.0
B [mm]	180.0