



(slika je simbolična)

## [krog. ventil ner.jeklo, 2-delno, IT/ET z navojem, G 1, DN 25](#)

Kategorija: [Stainless stell ball valve, 2-piece, IT/ET thread](#)  
Šifra: **135906RIE**

### Kratek opis

Stainless steel ball valve, 2-piece, IT/ET thread, G 1, DN 25,  
Operating temperature -20 °C to 180 °C, PN max. 63 bar

### Tehnične Specifikacije

|                               |  |
|-------------------------------|--|
| Min. delovna temperatura [°C] | -20  |
| Bore diameter padlock         | ca. 6.0 mm                                   |
| Krogelno tesnilo              | PTFE (15 % glass fibre reinforced)           |
| Krogla                        | Stainless steel 1.4401                       |
| Navoj                         | G 1  |
| Ohišje                        | Stainless steel 1.4408                       |
| Ročica                        | Stainless steel 1.4301, with plastic coating |
| Standardni navoj              | G thread acc. to DIN EN ISO 228-1            |
| Stebelno tesnilo              | PTFE   |
| C Ø [mm]                      | 25.0   |
| DN                            | 25   |
| PN [bar]                      | 63   |
| B [mm]                        | 69.0   |
| L [mm]                        | 85.0   |
| A [mm]                        | 125.0  |
| Max. delovna temperatura [°C] | 180  |