

Datum: 01.09.2024



(slika je simbolična)

Krog. ventil robustnejša oblika,metuljasta ročica, IT/ET, G/R 3/4

Kategorija: [Ball valve with butterfly handle, IT/ET](#)
Šifra: **103295RIE**

Kratek opis

Ball valve heavy duty design, Butterfly handle, IT/ET, nickel-plated brass, Operating temp. -20°C to 130°C, G/R 3/4, PN max 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

| | |
|-------------------------------|--|
| Min. delovna temperatura [°C] | -20 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Brass with a bare metal surface |
| Navoj | G/R 3/4 |
| Ohišje | Nickel-plated brass |
| Ročica - metuljček | Aluminium, painted black |
| Standardni navoj | G thread DIN EN ISO 228-1, R thread DIN EN 10226 (ISO 7-1) |
| Stebelno tesnilo | PTFE |
| F [mm] | 13.0 |
| E [mm] | 16.0 |
| DN | 20 |
| a/f 2 [mm] | 32 |
| a/f 1 [mm] | 33 |
| A [mm] | 55.0 |
| B [mm] | 58.5 |
| L [mm] | 77.0 |
| PN [bar] | 80 |
| Max. delovna temperatura [°C] | 130 |