

Datum: 02.10.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

[krog. ventil robustnejša oblika, Z ročico, ročni, IT/IT, G 1 1/2](#)

Kategorija: [Ball valve with hand lever, IT/IT](#)
Šifra: **103267RIE**

Kratek opis

Ball valve heavy duty design, Manual lever, IT/IT, nickel-plated brass, Operating temp. -20 °C to 130 °C, G 1 1/2, PN max. 80 bar

Applications: Compressed air, water, neutral and non-toxic gases, fuel oil (light distillate), fuel oil (heavy), lubricating oils, diesel oils.

Tehnične Specifikacije

| | |
|-------------------------------|-----------------------------------|
| Min. delovna temperatura [°C] | -20 |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Brass with a bare metal surface |
| Navoj | G 1 1/2 |
| Ohišje | Nickel-plated brass |
| Ročica | Aluminium, painted black |
| Standardni navoj | G thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo | PTFE |
| E [mm] | 18.0 |
| F [mm] | 18.0 |
| DN | 40 |
| a/f [mm] | 56 |
| PN [bar] | 80 |
| B [mm] | 103.0 |
| L [mm] | 103.0 |
| Max. delovna temperatura [°C] | 130 |
| A [mm] | 150.0 |