

Datum: 03.07.2024



(slika je simbolična)

Krog. ventil za vodo, z ročico, ročni, IT/IT, G 1 1/4, DN 32

Kategorija: [Potable water ball valves](#)Šifra: **133166RIE**

Kratek opis

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 1 1/4, DN 32, Operating temp. -15°C to 110°C, PN max. 40 bar
Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Aplikacije	Potable water, water
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass
Navoj	G 1 1/4
Ohišje	Nickel-plated brass (outside), brass (inside)
Ročica	Aluminium
Standardni navoj	Thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE / EPDM / HNBR
DN	32
PN [bar]	40
B [mm]	70.1
L [mm]	80.0
Max. delovna temperatura [°C]	110
A [mm]	130.0