

Datum: 24.08.2024



(slika je simbolična)

Krog. ventil za vodo, z ročico, ročni, IT/IT, G 3/8, DN 10

Kategorija: [Potable water ball valves](#)
Šifra: **133162RIE**

Kratek opis

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 3/8, DN 10, Operating temp. -15 °C to 110 °C, PN max. 50 bar
Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
Aplikacije	Potable water, water DIN EN 13828:2003-12, DVGW W 570
DVGW odobritev	PTFE
Krogelno tesnilo	Chrome-plated brass
Krogla	Brass
Material navojev	G 3/8
Navoj	Nickel-plated brass
Ohišje	(outside), brass (inside)
Ročica	Aluminium
Standardni navoj	Thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE / EPDM / HNBR
DN	10
B [mm]	42.0
L [mm]	50.0
PN [bar]	50
A [mm]	85.0
Max. delovna temperatura [°C]	110