

Datum: 27.09.2024



Krogelni ventil 3/2 »FUTURA«, zaklepni, Velikost 1, G 1/4

Kategorija: [Ball valves](#)
Šifra: **100283RIE**

(slika je simbolična)

Kratek opis

Ball valve 3/2-way »FUTURA«, lockable, Size 1, G 1/4,
Exhaust G 1/4, Input pressure max. 16 bar, Temperature -10
°C to 50 °C

Lockable ball valve, 3/2-way type including silencer,
mechanically operated.

Rotary switch can be turned 90°, with indication of
positions:

Horizontal: Input closed - outlet exhausted

Vertical: Flow open - exhaust closed

Exhaust air can be collected.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/4 At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Merjenje pretoka	G 1/4 PA66 GF60 Material: Die-cast zinc FUTURA Compressed air, neutral gases
Navoj	G 1/4
Ohišje	PA66 GF60
Priključni navoj	Material: Die-cast zinc FUTURA
Serijska	Compressed air, neutral gases
Srednje	
Velikost	1
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	52.0
C [mm]	54.5
B [mm]	87.5
Pretok [l/min]	1900