

Datum: 27.09.2024



## Krogelni ventil 3/2 »FUTURA«, zaklepni, Velikost 2, G 1/2

Kategorija: [Ball valves](#)  
Šifra: **100286RIE**

(slika je simbolična)

### Kratek opis

Ball valve 3/2-way »FUTURA«, lockable, Size 2, G 1/2,  
Exhaust G 1/2, Input pressure max. 16 bar, Temperature -10 °C to 50 °C  
Lockable ball valve, 3/2-way type including silencer, mechanically operated.  
Rotary switch can be turned 90°, with indication of positions:  
Horizontal: Input closed - outlet exhausted  
Vertical: Flow open - exhaust closed  
Exhaust air can be collected.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/2 At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Merjenje pretoka	G 1/2 PA66 GF60
Navoj	Material: Die-cast zinc
Ohišje	FUTURA
Priključni navoj	Compressed air, neutral gases
Serijska	2
Srednje	16
Velikost	50
Max. vhodni tlak [bar]	63.0
Max. temperaturno območje [°C]	70.5
A [mm]	127.0
C [mm]	14000
B [mm]	
Pretok [l/min]	